

# NCR P1532

## POS Terminal



### Never Takes a Day Off

The NCR P1532 POS terminal helps you serve customers quickly and efficiently, every day of the year. Built to endure the toughest environment, NCR P1532 will never let you down. NCR's newest generation of open retail platforms is faster, well-connected and uses less power than previous models. The terminal's value and consistent performance makes it the ideal terminal for multi-year roll-outs.

### Fast and Efficient

The P1532 POS terminal utilizes a next generation Intel® Celeron™ processor N3060 (Dual core, 2.48 GHz) that offers great performance and energy efficiency. The P1532 will be offered with a Windows 10 Operating System for NCR Counterpoint.

### Works Anywhere

All types of retailers will be able to save space with the countertop enclosure's small footprint and low profile.

### Continuous Operation

The retail hardened enclosure design offers a spill resistant, high impact housing that is built to withstand tough environments. Its fanless configuration reduces the amount of contaminants in the system, further extending the life span of the terminal.

For more information,  
visit [www.counterpointpos.com](http://www.counterpointpos.com), or call 800.852.5852.



# Why NCR?

NCR Corporation (NYSE: NCR) is the global leader in consumer transaction technologies, turning everyday interactions with businesses into exceptional experiences. With its software, hardware, and portfolio of services, NCR enables more than 550 million transactions daily across retail, financial, travel, hospitality, telecom and technology, and small business. NCR solutions run the everyday transactions that make your life easier.

NCR Counterpoint is the specialty retail management system that brings the front and back offices into harmony, enabling you to grow your best business. Our comprehensive and flexible solution will manage your business' details so you can focus on what truly matters: your customers. We build the stage that allows you to perform.

## Easy to See

Your staff can easily see the vivid 15-inch, (1024X768) LED and color display in either in the back office or on the sales floor. The resistive touchscreen provides an accurate and durable interface.

## Well-Connected

Connectivity is provided through four serial ports, four standard USB, one powered USB 12V which includes a standard USB port, one HDMI port, one display port, and one dedicated cash drawer port which supports dual 12v or 24v. Plus, powered serial ports eliminate the need for power bricks, thereby reducing another point of potential failure.

Technical Specification	
CPU	Intel® Celeron™ Processor N3060 (Dual core, 2.48 GHz)
Volatile Memory	4GB DDR3L Standard
Networking	Auto-selecting 10/100/1000 Base-T Ethernet using TCP/IP
Primary Display	15" XGA, LED 1024x768 LCD
Touch Screen	Support for 5-wire resistive
Storage	64GB SSD
Enclosure	Polycarbonate/ABS impact resistant, high strength blend, environmentally sealed

Technical Specification	
Dimensions (Countertop envelope through tilt angle)	13.6" L x 14.77" W x 14.67" H, 34.6 cm L x 37.5 cm W x 37.2 cm H (Note: with C730 customer display attached, length will be 20.19", 51.3 cm L)
Base Dimension	9.1" L x 8.9" W 23.1 cm L x 22.8 cm W
Tilt Angle	20° to 127° from vertical
Weight (15" with MSR/Stand)	14.5 lbs (6.58 kg) Varies by configuration. See Site Prep Guide for details.
Operation Temperature	32°F – 104°F, 0°C – 40°C
Storage Temperature	32°F – 113°F, 0°C – 45°C Must be in original pack material in humidity and temperature controlled environment
Humidity	5% to 85%, non-condensing

NCR continually improves products as new technologies and components become available. NCR, therefore, reserves the right to change specifications without prior notice.

All features, functions and operations described herein may not be marketed by NCR in all parts of the world. Consult your NCR representative or NCR office for the latest information.

All brand and product names appearing in this document are trademarks, registered trademarks or service marks of their respective holders.

